


特点Features

标准的3.2*2.5表面贴装形式
温度补偿晶体振荡器
电源电压1.8 ~ 3.3V
包装：每卷3000PCS
Tpical 3.2 × 2.5mm SMD package
Temperature Compensated Quartz Crystal Oscillators
Supply Voltage: 1.8 V ~ 3.3 V.
Packing:Tape&Reel,3000 pcs per Reel



标准规格Electronic Specification

型号 Type	TCXO 3225	
频率范围 Frequency Range	13 ~ 52 MHz	
输出类型 Output Type	Clipped Sinewave	
输出负载 Output Load	10K Ω //10 pF	
振荡模式 Oscillation Mode	Fundamental	
供电电压 Supply Voltage	1.8 ~ 3.3 V	
输出电压 Clipped Sinewave Output Voltage	0.8 V _{p-p} typical	
频率稳定性 Frequency Stability	Vs. Temperature (– 30 ~ + 85 ° C)	± 0.5/ ± 2.0 ppm
	Vs. Load (Load varies ± 10 %)	± 0.2 ppm Max.
	Vs. Supply Voltage (V _{cc} = Typical ± 0.1 V)	± 0.2 ppm Max.
频率容限 Frequency Tolerance	at 25 ° C after 2 Reflows with Typical Applied to Auto Frequency Control Pin	± 2.5 ppm Max.
频率漂移 Slope of Frequency Drift	± 0.1 ppm / ° C Typical; ± 0.5 ppm / ° C Max.	
储存温度范围 Storage Temperature Range	–40 ~ + 85 ° C	
自动频率控制范围 Auto Frequency Control (AFC) Range	± 7 – ± 16 ppm (1.4 ± 1V)	
电源电流 Supply Current	2.0 mA Max.	
启动时间 Start–up Time	5 ms Max.	
谐波 Harmonics	–5 dBc Max.	
相位噪声 Phase Noise at 1 kHz offset	–130dBc/Hz	
老化 Aging (at 25 ° C)	± 1 ppm / year Max.	

外型尺寸Outline Dimensions(Unit:mm)

